

(mnoclean)

Hospital Grade Air Purification System





General air purification purpose. Application area: Office, Home, School, elderly House and Restaurant etc...

Hospital Grade – Model: 300A / B MultiTrap (Positive / Negative Pressure Design)

Electrostatic Pre-filter + Antimicrobial Filter (EPA – US Registered Coating) + True HEPA Filter (H13 – EN1822 Grade)+ Absorption Carbon Filter + Photo Catalytic Filter Set + Nano Silver Antimicrobial Filter + MnO2 Catalytic Carbon Filter + UVC Sterilizing Lamp + Anion Generation

Timer Setting + Remote Control + 3 Speed Setting + Movable Roller + Wall Mount Set (Option) + LED Display + Safety Door Lock



Free Standing with Roller or Wall Mount



300A

MultiTrap



300B MultiTrap

Model:

300A / B MultiTrap

For general air purification purpose, including all standard 10 Individual Filtration Filter and UV lamp, with additional IC

Pro Nano-Silver Antimicrobial Filter and IC Pro 20mm TRUE HEPA Filter – H13 (EN1822) Standard.

Function:

Removes airborne pollutants, including dust, pollen, unpleasant smells, toxic gas, chemical e.g. most common VOC & formaldehyde and also Bacteria & Virus.

Special Feature:

IC Pro Nano-Silver Antimicrobial Filter to increase the efficiency of bacteria and virus kill.

IC Pro 20mm TRUE HEPA Filter - H13 (EN1822) Standard to increase the efficiency of dusts and bacteria trap.

Suitable area:

Office, Factory, School, Elderly Home, Pet Shop, Bar, Restaurant etc...

Why "innoclean" are professional and as a hospital grade air purifier

All the filters system of "innoclean" 400 & 300 are 5/. Professional design of "UV Reflection Chamber" to increase much 1/. designed in Individual, more times of UV intensity to kill bacteria & virus 2/. Could create Positive or Negative pressure for area 6/. Multi-function design in one machine, can solve the 3 main request high level of purification and prevent pollutant in indoor air - bacteria & virus; dust and toxic gas & odor cross-contamination 3/. Different certificate & Testing Report to prove the 7/. All machine with individual Certificate of Quality Performance efficiency Use with H13 Grade EN1822 Standard True HEPA 4/. 8/. Widely used in HK including hospital, clinic and government office filter (Standard for hospital & cleanroom)

Hospital Grade – Model: 300A / B MultiTrap

Certificate & Report

CE, CQC, ISO9001 Center For Disease Control and Prevention CDC Testing Report Beijing Tsing Hua University Develop & Testing Report The Hong Kong Polytechnic University Testing Report (Catalytic Filter) Hong Kong Standard & Testing Center Report (Catalytic Filter) LWAN IAQ Testing Report - Hong Kong HKAPC IAQ Testing Report - Hong Kong US Environmental Protection Dept.Registered (Antimicrobial Coating) IAQ Consultant Testing Center - Singapore





Product specifications

Model	300A MultiTrap and 300B MultiTrap
Power requirement	220V/50Hz(60Hz) / (110V Options)
Power consumption	MAX: 50W
Noise level	< 50 dB (Max.)
Negative ion output	1×10^{6} /cm ³
Air flow rate	330 M3/Hr
Service Area	Up to 1,100 sq.ft.
Service Area	1,1000 sq.ft. (Purify the area within 1 hour)
Service Area	800 sq.ft. (Purify the area within 45 minutes)
Service Area	400 sq.ft. (Purify the area within 22 minutes)
Pollutant removal capability	
Microorganism removal	99.5%
VOC removal	96.2%
Formaldehyde removal	95.5%
Benzene removal	85%
0.3 micro-meter Dust removal	99.97%
0.1 micro-meter Dust removal	65.9%
General Odor removal	83%
Key parts of the product	0070
Electrostatic Pre-filter	YES
Antimicrobial Pre-filter	YES
Woven Carbon Filter	YES
True HEPA Filter	YES
	YES
Photo catalyst Chamber Nano Silver Antimicrobial Filter	YES
MnO2 Catalytic Carbon Filter	YES
253.7 nm UVC Sterilizing Lamp	YES
Anion Generator	YES
Display panel LED Icon	YES
Remote Control	TES
	VES
Ultra Remote Control	YES
Function settings	-
Fan speeds	L/M/H
Timer Timer Setting	$\frac{1}{1}$ hr $\frac{1}{2}$ hro $\frac{1}{4}$ hro
Timer Setting Safety Door Lock	1 hr / 2 hrs / 4 hrs
	VES
Door Lock for Front Cover	YES
Roller Easy Movable Roller	YES
Colour / Dimensions / Weight	1L0
Colour / Dimensions / Weight	- Silver with White Front Cover / Blue with White Front Cover
	850mm x 400mm x 290mm
Dimensions(H x W x D) mm	
Weight	15kg
FREE Warranty	1 year including parts (Excluding consumable parts)
Limited Warranty	Life Warranty
Optional Accessories	
Wall Mount Frame	For wall mount purpose
FlexVent - IN	For creation of Positive or Negative Pressure purpose

All systems come complete with full filter sets, remote controller, operation manual, 6 foot power cord, certified label and certificate of quality performance.